



RÉGÉNÉRATEUR DE PURETÉ

DI - range *-Cold Plasma for Central Air Treatment Units -*



The DI-range application is mainly for industrial & collective use for the neutralization of bacteria, viruses and smells.

The DI-range allows a very easy integration in buildings, directly in ventilation ducts.

One torch can treat an air flow of 1500m³/hour.

The DI-range is can have 4 to 8 torches.

Solutions for installations with large air volumes:

- Suitable for commercial and industrial installations
- Integrates easily with existing equipment
- Low maintenance and low energy consumption
- Allows to reduce the rate of air renewal (significant energy savings)



RÉGÉNÉRATEUR DE PURETÉ

Technical details :

Type	DI -Range		
Module	DI 4	DI 6	DI 8
Dimension in mm	310 x 120 x 210	430 x 120 x 210	550 x 120 x 210
Weight in Kg	7.6	11.5	14.5
Processing flow	From 4800 till 6000 m ³ /h	From 7200 till 9000 m ³ /h	From 9600 till 12000 m ³ /h
Consumption in W	1	1.5	1.5
Power	AC 240V/50Hz		

Examples of applications:



Hotels
Restaurants
Casinos
Libraries
Schools
Laboratories
Agri-food industries
Office buildings
Hospitals